

# 868&915MHz 10W Signal Booster Product Specification Sheet

## EP-AB075

### 1. Product Description

This product is a 868 & 915MHz 10W bidirectional power amplifier (one transmitting channel and one receiving channel), specifically developed for 868/915MHz wireless data and video transmission applications.

It utilizes advanced single-carrier modulation technology to significantly extend wireless communication distance while maintaining transmission rate, and offers strong anti-interference capability.

The product features a compact size, high efficiency, excellent linearity, and reliable stability, making it widely applicable in emergency communications, wireless security, and power systems.



### 2. Applications

- Smart Home System Signal Extension
- Wireless Camera Range Extension
- Drone Communication Range Extension
- Industrial and Emergency Communication Enhancement

### 3. Features

- Up to 10W high output power, enhancing signal coverage and link stability
- Ultra-low noise figure (<1.2 dB) ensures superior signal reception performance
- Wide 12V - 24V DC operating range, adaptable to various power environments
- Plug-and-play design, no software configuration required
- Durable aluminum alloy enclosure, providing superior heat dissipation and protection
- Compact and lightweight, suitable for embedded and mobile applications

### Parameters

Number	Items	Specifications
1	Frequency Range	850 - 930MHz
2	Operating Voltage	12-24V
3	Receiving Gain	18dB ± 1
4	Transmission Gain	20dB ± 1
5	Max Output Power(P1dB)	40dBm(10W)

6	Input Trigger Power	Min:4dBm Max:20dBm
7	Linear Output Power	35dBm, EVM $\leq$ 5% (802.11g 54Mbps, 64QAM, BW 20MHz)
8	Noise Figure	<1.2dB
9	Current Supply	650 mA @ Pout 35dBm, 12V
10	TX/RX Switch Time Delay	<1 us
11	LED Indicator	Red (Power/Status)
12	Operating Temperature	-40℃ $\sim$ +70℃
13	Storage Temperature	-40℃ $\sim$ +125℃
14	Operating Humidity	$\leq$ 95% RH (non-condensing)
15	RF Connector	Input: SMA-K; Output: RPSMA-K
16	Power Socket	Ø2.5*0.7mm
17	Dimensions (L×W×H)	73*43*15(mm)
18	Housing Material	Aluminum
19	Net Weight	0.085kg