

Product Features

- Four external 3dBi omnidirectional antennas
- Supports Repeater Mode and AP Mode
- Built-in 100~240V 50/60Hz AC power module, no need for an external power adapter
- Detachable multi-standard plug supports CN, EU, US, UK plug types
- Dual-band 1200Mbps (2.4GHz + 5.8GHz), high anti-interference, faster and more stable wireless transmission
- One RJ45 port supports wireless-to-wired networking (e.g., desktop, laptop)
- Professional smart WiFi repeater, supports automatic WiFi hotspot scanning and memory function
- Web-based setup with bilingual (Chinese/English) interface and one-click

configuration

Product Specifications

| Product Name | | 1200M Dual-Band Wireless Repeater | |
|----------------------------|------------------------|---|--|
| Model | | EP-AC2985 | |
| Hardware Specifications | | | |
| Hardware | Main Chipset | MT7628DAN+MT7613BEN | |
| | RAM | 64MB | |
| | FLASH | 8MB | |
| | PA | Built-in | |
| Wireless Parameters | Standards | IEEE 802.11ac, backward compatible with 802.11a/b/g/n | |
| | Frequency Bands | Dual-band (2.4GHz and 5.8GHz) | |
| | Speed | 1200Mbps(2.4 GHz: 300 Mbps + 5.8 GHz: 867 Mbps) | |
| | Transmit Power | 2.4 GHz: 18dBm ± 1 dBm 5.8 GHz: 20dBm ± 1 dBm | |
| | Antenna Gain | 5.8G: 3dBi*2 omnidirectional 2.4G: 3dBi*2 omnidirectional | |
| | Receive Sensitivity | $-90dBm \pm 2 dBm$ | |
| Interfaces | LAN Port | 1 个 10/100Mbps LAN 端口 | |
| interfaces | Button | 1 个复位键/WPS 键 | |
| Indicators | LED Indicators | SYS / LAN / Repeater | |
| Dawar Supply | Input | AC 100~240V 50/60Hz | |
| Power Supply & Consumption | Plug Type | Detachable, supports CN/US/EU/UK standards | |
| | Power Consumption | < 6W | |
| A : | Main Unit | 1*1200M Dual-Band Repeater | |
| Accessories | Others | User Manual*1, Warranty Card*1, Certificate*1 | |
| | Product Dimensions | 196mm*90mm*32mm (L*W*H) | |
| | Color | White | |
| Appearance & Packaging | Weight | 100g | |
| | Package Dimensions | 212*97*76mm (L*W*H) | |
| | Carton Dimensions | 640*485*305cm (L*W*H) | |
| | Packing Quantity | 60pcs/carton | |
| Other | Coverage Area | 0~80 m² | |
| | Operating Environment | Temperature: -10°C to 55°C (Operating), -40°C to 70°C (Storage) Humidity: 10%–90% RH (Operating), 5%–95% RH (Storage), | |

1200M Dual-Band Wireless Repeater

| _ | | non-condensing | |
|-------------------------|----------------------|--|--|
| Software Specifications | | | |
| Network | Operating Modes | Repeater Mode, AP Mode | |
| Wireless | Wireless Security | WPA2, WPA, WPA2-PSK (AES), WEP encryption | |
| Security | | | |
| Other | Product Features | A professional smart Wi-Fi repeater with automatic hotspot scanning and memory function for previously connected Wi-Fi networks Supports dual-band concurrent connections on both 2.4 GHz and 5.8 GHz, delivering wider coverage, faster and more stable transmission, and enhanced resistance to interference. | |
| | User Limit | Supports up to 35 users | |
| | System Language | Chinese / English switchable | |
| | Management Interface | Web-based configuration | |
| | Application | Homes, duplexes, multi-floor homes, rental rooms, apartments, | |
| | Scenarios | villas, etc | |

Product Size

